



**WACKER  
NEUSON**  
*all it takes!*



**BS60-2i**  
5000009339

Home >> Catalog >> Products >> Compaction >> Vibratory Rammers >> 2 Stroke Rammer >> BS60-2i



### **BS60-2i**

Material number 5000009339

Oil-injected, 2-stroke rammer with 11-inch (280 mm) shoe for soil compaction

### **Product details**

- Patented oil-injection system offers a no-mix system providing convenience and reliable performance
- Fuel to oil ratio of 120:1 allows for longer and cleaner running times, up to 100 hours on a single tank of oil
- Low oil shutdown prevents running the rammer without oil for trouble free operation
- Powered by the exclusive WM 80, two-stroke engine, specifically designed by Wacker Neuson with withstand rugged rammer applications, meets all emission standards
- Simple operation and easy starting
- Unique four-stage air filtration system provides longer life and improved durability

### **Comes with**

Includes operator's manual

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

## Technical specifications

### BS60-2i

#### ENGINE

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	two-stroke
Cylinder capacity	80 cm <sup>3</sup>
Fuel	Alkylate fuel/Oil mixture
Fuel management	Carburettor
Fuel consumption	1,00 L/hr
Cylinder	1
Tank capacity	3,00 l
Standard (Effective power)	ISO 3046-1
Nominal Engine speed	4.400 1/min
Effective power	1,8 KW
Idling speed	2.000 1/min
Starter type	Recoil starter
Engine Manufacturer	Wacker Neuson

#### MECHANICAL - OUTPUT DETAILS

Number of blows	700 1/min
-----------------	-----------

#### MECHANICAL DETAILS

Length	673 mm
Length Ramming Shoe	330 mm
Width	343 mm
Width Ramming Shoe	280 mm
Height	965 mm
Operating weight	66,0 kg
stroke at tamper	80 mm

#### MECHANICAL DETAILS

Length	26,5 "
--------	--------

Length Ramming Shoe	13,0 "
Width Ramming Shoe	11,0 "
Width	13,5 "
Height	38,0 "
Operating weight	145,5 lb
stroke at tamper	3,1 "

MECHANICAL - OUTPUT DETAILS

Number of blows	700 1/min
-----------------	-----------

ENGINE

Fuel consumption	0,3 GPH US
Engine operating mode	two-stroke
Engine type	Gasoline engine
Fuel	Alkylate fuel/Oil mixture
Cooling	air cooling
Cylinder	1
Cylinder capacity	4,9 Inch <sup>3</sup>
Fuel management	Carburettor
Nominal Engine speed	4.400 1/min
Standard (Effective power)	ISO 3046-1
Effective power	2,4 hp
Idling speed	2.000 1/min
Starter type	Recoil starter
Engine Manufacturer	Wacker Neuson
Tank capacity	0,8 gal US

OPERATING FLUIDS

Tank capacity	3,00 l
---------------	--------

OPERATING FLUIDS

Tank capacity	0,8 gal US
---------------	------------