

Table 4.3a Specifications and Features

MODEL	3215	3219	3220	3226
Weight *	2400 lb. 1089 kg	2580 lb. 1170 kg	3510 lb. 1592 kg	4135 lb. 1876 kg
Overall width	32" 0.81 m		32" 0.81 m	
Overall length	70.0" 1.78 m		91" 2.3 m	
Platform Size (inside)	26" x 64" 0.66 m x 1.63 m		28" x 83" 0.71 x 2.1 m	
Height				
Working Height	21' 6.4 m	25' 7.6 m	26' 8.1 m	32' 9.9 m
Platform Elevated Height	15' 4.6 m	19' 5.8 m	20' 6.1 m	26' 7.9 m
Stowed Platform Height	34.5" 0.88 m	39" 0.99 m	38" 0.97 m	45" 1.1 m
Stowed Height (Railings Up)	74" 1.88 m	78.5" 1.99 m	82" 2.1 m	89" 2.3 m
Drive Height	FULL			
Standard Operating Time				
Lift Time (No Load)	18 s	20 s	27 s	47 s
Lower Time (No Load)	32 s	39 s	41 s	63 s
Lift Time (Rated Load)	23 s	25 s	33 s	51 s
Lower Time (Rated Load)	24 s	29 s	29 s	46 s
Chassis				
Normal Drive Speed	2 mph 3.2 km/h		1.9 mph 3.0 km/h	2.4 mph 3.8 km/h
Elevated Drive Speed	0.65 mph 1.05 km/h		0.64 mph 1.0 km/h	0.64 mph 1.0 km/h
High Torque Drive Speed	N/A		0.95 mph 1.5 km/h	1.2 mph 1.9 km/h
Gradeability (Ramp Angle)	23%		25%	
Tires	12 x 4 x 8 Solid Rubber		16 x 5 x 12 Solid Rubber	
Hydraulic Oil				
Type	ATF Dexron III		ATF Dexron III	
Tank Capacity	2.9 gal. 10.9 L		7.93 gal. 30 L	

SJIII T4.3a - 133173AM

* Weight with standard 3' (0.9 m) or 4' (1.2 m) extension platform.
Refer to nameplate for aerial platforms with 5' (1.5 m) or 6' (1.8 m) extension platform.

Skyjack 20-23

Table 1-1b. Specifications and Features - The Compacts

Model	3015	3219
Weight Ω	2360 lbs. (1070 kg)	2790 lbs. (1266 kg)
Width	30.50" (0.77m)	32.50" (0.83m)
Length	66.50" (1.69m)	66.50" (1.69m)
Elevated Working Height	21.00' (6.4m)	25.00' (7.6m)
Elevated Platform Height	15.00' (4.6m)	19.00' (5.80m)
Stowed Fixed Railing Height	78.0" (1.98m)	79.0" (2.01m)
Drive Height	Refer to "Table 2.6. Limit Switch Settings"	
Platform Size	28" x 64" (0.71x1.63m)	28" x 64" (0.71x1.63m)
High Travel Speed	2 mph (3.2 km/h)	2 mph (3.2 km/h)
Elevated Drive Speed	.75 mph (1.2 km/h)	.75 mph (1.2 km/h)
Lift Time (No Load)	21 sec.	30 sec.
Lower Time (No Load)	29 sec.	40 sec.
Gradability	20%	20%

Ω Weight with standard 3' (0.9m) extension platform.
(Refer to nameplate for machines with 3' (0.9m) powered extension platform, CE models and other options.)