

ROUGH TERRAIN SERIES

ANSI/CSA SPECIFICATIONS

MODEL	Work Height (Nom.)	Raised Height (Nom.)	Lowered Platform Height	O/A Width	O/A Length	Stowed Height ***	% Gradeability (stowed)	Capacity lbs(kg)	Platform Size	Tire	Travel Speed High (mph)	Lift Speed (sec.) (nom.)	Weight lbs (kg)
S J 6 0 0 S E R I E S													
7027	33' (10.1m)	27' (8.2m)	60" (1.52m)	70" (1.78m)	119" (3.02m)	101" (2.57m)	35%	1500 (680kg)	65" x 112.5" (1.65 x 2.86m)	*	3 (4.8km/h)	31	7600 (3447kg)
S J 8 0 0 S E R I E S													
8831	37' (11.3m)	31' (9.4m)	59" (1.50m)	87" (2.21m)	137.5" (3.49m)	102" (2.59m)	30%	2500 (1134kg)	70" x 138" (1.78 x 3.51m)	*	3 (4.8km/h)	62	9757 (4426kg)
8841	47' (14.3m)	41' (12.5m)	69" (1.75m)	87" (2.21m)	137.5" (3.49m)	113" (2.87m)	30%	1500 (680kg)	70" x 138" (1.78 x 3.51m)	*	3 (4.8km/h)	67	10760 (4881kg)
S J 8 0 0 E L E C T R I C													
8831E	37' (11.3m)	31' (9.4m)	59" (1.50m)	87" (2.21m)	137.5" (3.49m)	102" (2.59m)	30%	2500 (1134kg)	70" x 138" (1.78 x 3.51m)	*	3 (4.8km/h)	62	10257 (4653kg)
8841E	47' (14.3m)	41' (12.5m)	69" (1.75m)	87" (2.21m)	137.5" (3.49m)	113" (2.87m)	30%	1500 (680kg)	70" x 138" (1.78 x 3.51m)	*	3 (4.8km/h)	67	11260 (5108kg)
S J 1 0 0 0 S E R I E S													
9250	56' (17.1m)	50' (15.2m)	79" (2.01m)	92" (2.34m)	176" (4.47m)	123" (3.12m)	25%	2000 (907kg)	74" x 168" (1.88 x 4.27m)	*	2 (3.2km/h)	67	13,380 (6069kg)
9250F	56' (17.1m)	50' (15.2m)	79" (2.01m)	92" (2.34m)	176" (4.47m)	123" (3.12m)	25%	2000 (907kg)	74" x 168" (1.88 x 4.27m)	o	2 (3.2km/h)	67	14,500 (6577kg)
9250A	56' (17.1m)	50' (15.2m)	79" (2.01m)	88.25" (2.24m)	176" (4.47m)	123" (3.12m)	25%	1350 (612kg)	74" x 168" (1.88 x 4.27m)	o	2 (3.2km/h)	67	14,500 (6577kg)
9250AL	56' (17.1m)	50' (15.2m)	79" (2.01m)	92" (2.34m)	176" (4.47m)	123" (3.12m)	25%	1350 (612kg)	74" x 168" (1.88 x 4.27m)	o	2 (3.2km/h)	67	14,500 (6577kg)

* Type 6 - 10 x 16.5, 6-ply grip lug (air)

** Hinged rails standard; height 33" less with rails folded down

† Type 6F - 10 x 16.5, 6-ply grip lug tubeless foam filled tires



Air tires not available for these models

*** Add 7 1/2" to stowed height for units with optional deck extensions

† Add 500lbs to overall weight for each optional deck extension.

†† Capacities differ for some models when equipped with extensions and/or optional tire types (Consult factory for details)

UNIVERSAL FEATURES



- a) Joystick controller
- b) Hinged rails
- c) Slide out battery compartment (800E)
- d) Lockable cabinets with swing out doors
- e) Color coded numbered wiring system and hourmeter
- f) 110V GFI AC outlet to platform
- g) Safety belt lanyard attachment rings (4)
- h) Slide-out engine for superior accessibility
- Independent levelling outriggers (standard on 9250 - not available on 7027)
- Flashing amber warning light
- Liquid-cooled dual fuel or diesel engine
- Operator horn
- Tilt alarm with drive/lift cut out
- Comprehensive Operation Parts and Service Manual
- Complies with ANSI and CSA standards

OPTIONAL EQUIPMENT



Deck extension

- Movement alarm
- Deck extension (manual and powered)
- 4-Wheel drive
- Tire options:
 - #6 F tires - 10 x 16.5, 6 ply lug (foam) - (600 & 800 only)
 - #7 tires - 31 x 15.5, 8 ply super terra (air) - (600 & 800 only)
 - #7 F tires - 31 x 15.5, 8 ply super terra (foam) - (600 & 800 only)

This literature is for illustrative purposes only. Consult Part/Operating & Service manuals for proper procedures. Work platforms have been tested with applicable standards as interpreted by Skyjack. Specifications subject to change without notice.

