

SPECIFICATIONS

Model		SSV65	SSV75		
Type of operator station		Open CAB / Closed CAB	Open CAB / Closed CAB		
Engine	Model	V2607-CR-TE4	V3307-CR-TE4		
	Emission certification	Tier 4	Tier 4		
	Gross HP (SAE J1995)	HP (kW)/rpm	64.0 (47.7)/2700	74.3 (55.4)/2600	
	Net HP (SAE J1349)	HP (kW)/rpm	63.0 (47.0)/2700	73.2 (54.6)/2600	
	Displacement	cu.in. (cc)	159.7 (2615)	203.3 (3331)	
	Cylinders		4	4	
	Bore Stroke	in.(mm)	3.5 (87) × 4.4 (110)	3.8 (94) × 4.8 (120)	
Loader performance	Aspiration		Turbocharged	Turbocharged	
	Rated operating capacity-50% tipping load		lbs. (kg)	1950 (885)	2690 (1220)
	Tipping load		lbs. (kg)	3900 (1770)	5380 (2440)
	Breakout force	Bucket	lbf. (kgf)	4839 (2195)	5884 (2669)
		Lift arm	lbf. (kgf)	3858 (1750)	4850 (2200)
Lift arm path			Vertical	Vertical	
Power train	Standard tire size		10-16.5-8PR	12-16.5-10PR	
	Chain size ASA#		80	100	
	Travel speed	Low	mph (km/h)	6.9 (11.1)	7.4 (11.9)
		High	mph (km/h)	11.1 (17.8)	11.8 (19.0)
	Traction force		lbf. (kgf)	7339 (3329)	8494 (3853)
Ground clearance		in. (mm)	7.6 (193)	8.1 (207)	
Hydraulic system	Loader hydraulic flow		gpm (ℓ/min.)	18.0 (68.0)	20.9 (79.0)
	Loader hydraulic pressure		psi (kgf/cm ²)	3271 (230)	3271 (230)
	Aux. hydraulic flow	Standard	gpm (ℓ/min.)	18.0 (68.0)	20.9 (79.0)
		High	gpm (ℓ/min.)	28.0 (106.0)	30.4 (115.0)
Service refill capacities	Hydraulic tank		gal. (ℓ)	4.2 (16.0)	4.2 (16.0)
	Fuel tank		gal. (ℓ)	25.4 (96.0)	26.9 (102.0)
Operating weight (Include operator weight 175 lbs.)		lbs. (kg)	6790 (3080) / 7055 (3200)	8157 (3700) / 8422 (3820)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.

DIMENSIONS

SSV65 / SSV75

