

# 830P

PUSH AROUND MAST LIFT

**JLG**  
reachingout®

## Performance

Platform Height	8 ft 2 in.	2.5 m
Working Height	14 ft 2 in.	4.32 m
Stowed Height	61.4 in.	1.56 m
Platform Entry Height	14 in.	.36 m
Platform Size (W x L)	28.7 in. x 39.3 in.	.75 x 1.0 m
Overall Vehicle Length	47 in.	1.19 m
Overall Vehicle Width	29.5 in.	.75 m
Gross Vehicle Weight	628 lb	285 kg
Platform Capacity	440 lb	200 kg

## Standard Specifications

### Power Source

Batteries	12V DC AGM Battery
Battery Charger	Automatic 110V-240V Charger

## Standard Features

- Auto-Lok Wheels on Elevation
- Non-Marking Wheels
- Rust-Free Tilt-Up Aluminum Platform
- Protective Wall Bumpers
- Tool Tray
- Frame-Mounted Bubble Level
- Service Prop
- Integrated Fork Pockets
- Detachable Platform Controls with Coil Cable
- Heavy Duty Ultra-Glide Lifting Mast

## Accessories & Options

- 110 V or 230V Main Power
- Tilt Alarm with Auto Cut-Out
- Protective Storage Covers



**JLG**

**JLG Industries, Inc.**  
1 JLG Drive  
McConnellsburg, PA 17233-9533  
Telephone 717-485-5161  
Toll-free in US 877-JLG-LIFT  
Fax 717-485-6417  
[www.jlg.com](http://www.jlg.com)

**An Oshkosh Corporation Company**

## The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Part No.: 3132132  
R021802  
Printed in USA